

## Veggplugg

Bestillingsnr. 363



- Skrukontakt

## Tekniske spesifikasjoner

|                 |             |
|-----------------|-------------|
| Ampere          | 125 A       |
| Poler           | 4 p         |
| Volt            | 230 V       |
| Klokkeposisjon  | 9 h         |
| Hertz           | 50-60 Hz    |
| Tilkoblingsmåte | skrukontakt |
| Kontakt         | standard    |
| Kapslingsgrad   | IP67        |
| Vekt            | 2061 g      |
| Kontrollmerke   | EAC, CQC    |

## Dimensjoner



| Drawing   | Amp.  | 63    |       |     | 125 |   |
|---|-------|-------|-------|-----|-----|---|
|   |       | Poles |       |     | 4   | 5 |
| 2 MB 36   |       | 3     | 4     | 5   | 4   | 5 |
| Dim. in mm  |       |       |       |     |     |   |
| a   | 170   | 170   | 170   | 264 | 264 |   |
| b   | 118   | 118   | 118   | 163 | 163 |   |
| c   | 171   | 171   | 171   | 205 | 205 |   |
| d   | 134.5 | 134.5 | 134.5 | 240 | 240 |   |
| e   | 103   | 103   | 103   | 140 | 140 |   |
| f   | 6,1   | 6,1   | 6,1   | 8,1 | 8,1 |   |
| g   | 6     | 6     | 6     | 8   | 8   |   |
| h   | 250   | 250   | 250   | 355 | 355 |   |
| M   | 40    | 40    | 40    | 50  | 50  |   |
| M*  | 2x40  | 2x40  | 2x40  | 50  | 50  |   |
| α   | 25°   | 25°   | 25°   | 20° | 20° |   |
| Max. cable diam. (mm)   | 27    | 27    | 27    | 38  | 38  |   |
| Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. | 6     | 6     | 6     | 16  | 16  |   |
|   | -16   | -16   | -16   | -35 | -35 |   |